

Search for $KL0 \rightarrow \pi^0 \nu \bar{\nu}$ Decay (KLOD project at IHEP).

A.Kurilin

Joint Institute for Nuclear Research
JINR, Dubna

	BNL	Fermilab		KEK	
	KOPIO	KTeV-99	KAMI	E391A	JHF
Proton energy	24 GeV	800 GeV	120 GeV	12 GeV	50 GeV
Protons/pulse	5×10^{13}	1×10^{13}	3×10^{13}	2×10^{12}	2×10^{14}
Cycle time	3.6 sec	80 sec	2.9 sec	2.5 sec	3.42 sec
Flat-Top	1.6 sec	40 sec	1.0 sec	0.5 sec	0.75 sec
Ext.angle	45°	4.8 mr	24 mr	4°	10°
Beam profile	$4\text{mr} \times 125\text{mr}$	$0.22\text{mr} \times 0.22\text{mr}$	$0.6\text{mr} \times 0.6\text{mr}$	4 mr^ϕ	2.6 mr^ϕ
Solid Angle	$500\text{ }\mu\text{str}$	$0.048\text{ }\mu\text{str}$	$1\text{ }\mu\text{str}$	$12.6\text{ }\mu\text{str}$	$5.5\text{ }\mu\text{str}$
$Y_{K_L^0}/\text{p/str}$	4.8×10^{-3}	4.8×10^2	3.7	5.9×10^{-2}	0.96
Av. K_L^0 mom.	$0.7\text{ GeV}/c$	$70\text{ GeV}/c$	$10\text{ GeV}/c$	$2\text{ GeV}/c$	$2\text{ GeV}/c$
Decay region	3.5 m	38 m	34 m	2.7 m	2.7 m
Decay prob.	16 %	2.1 %	10 %	4.3 %	4.3 %
K_L^0/pulse	1.2×10^8	2.3×10^7	1.1×10^8	1.5×10^6	1.1×10^9
K_L^0 -decay/pulse	1.9×10^7	4.8×10^5	1.1×10^7	6.5×10^4	4.7×10^7
Av. K_L^0 -decay/sec	5.3×10^6	6×10^3	3.8×10^6	2.6×10^4	1.4×10^7
Inst.decay-rate	12 MHz	12 kHz	11 MHz	130 kHz	63 MHz
Acceptance	1.6 %	5 %	7.4 %	8 %	16 %
Run Time	$3 \times 10^7\text{ sec}$	$6 \times 10^5\text{ sec}$	$3 \times 10^7\text{ sec}$	$1 \times 10^7\text{ sec}$	$3 \times 10^7\text{ sec}$
Running Eff.	50 %	50 %	50 %	50 %	50 %
Sensitivity	7.8×10^{-13}	1.1×10^{-8}	2.3×10^{-13}	1.0×10^{-10}	3.0×10^{-14}
Events(3×10^{-11})	38 events		130 events		1000 events

• KTeV



• KAMI

• KOPIO
????

• E391A

• JHF (JPARK)


Beam line K_L at U-70 IHEP




2004/8/3

10^{13} 60 GeV p/cycle, Cu-target 25 cm (80% interaction), 35 mrad, Pb 5cm

Beam line KL at U-70 IHEP




“n” and “ γ ” background





	Интенсивности			Отношения		
	K_L^0	n	γ	n/K_L^0	γ/K_L^0	γ/n
Без конвертера	$7.7 \cdot 10^7$	$8.3 \cdot 10^8$	$3.1 \cdot 10^{10}$	11	402	37
С конвертером	$5.4 \cdot 10^7$	$5.2 \cdot 10^8$	$7.4 \cdot 10^8$	10	14	1.4


KLOD setup






KLOD setup







KLOD setup



Veto barrel (I)



Veto detectors (I)



Veto barrel (II)


Inefficiency of γ detection:

- “Punch-through” @ >1 GeV $\Rightarrow 18 X_0 \Rightarrow 8 \times 10^{-7}$
- **Photonuclear reactions**
@ $(0.1 \div 1)$ GeV $(10^{-4} \div 10^{-6})$ for 10 MeV threshold
 $\Rightarrow$ reduction of threshold
- «Sampling»-effect @ <100 MeV
 $\sim 1\%$ @ 20 MeV for (1 mm Pb + 5 mm Scintil.)
 $\Rightarrow$ «thin» structure
 $\Rightarrow$ reduction of threshold


«Shashlik» - calorimeter

(0.3 mm Pb + 1.5 mm scintillator)


- 30000 photons/ 1 GeV γ
- 5.5 ph.e./plate/ *mip*
- 18 ph.e./ 1 MeV «visible» energy
- $\sigma_E/E \approx 3\%/\sqrt{E}$




Size of module along beam	300 mm	Segmentation along beam – 100 mm
Size of module across beam	200 mm	
Scintillator thickness	1.5 mm	
Lead thickness	0.275 mm	0.55 mm for first part
Radiation length, X_0	35.5 mm	17.75 mm for second part
Length of module (active part)	500 mm	(355 + 145) mm, (10 + 8) X_0
Full length of module	600 mm	Without PMT
Weight of module	80 kg	
Length of fibres/module	268 m	
Total of modules veto	1400	(28 -- across beam) x (50 -- along)
Full length of fibres (veto)	375 km	




А (Бумага поз.31 и лента поз.30
условно не показаны)




С-С




В (Бумага поз.31 и лента поз.30
условно не показаны)




Ф (4:1)




Д (5:1)



Е (5:1)



Г (4:1)



Техническая характеристика

1.Количество сцинтилляционных пластин (шт)	~300
2.Количество свинцовых пластин (шт)	~299
3.Количество бумажных пластин (шт)	~600
4.Диаметр волокна (мм)	~1
5.Средний вес свинцовых пластин (кг)	~17.3
6.Средний вес сцинтилляционных пластин (кг)	~5.7
7.Вес модуля (кг)	~18.2
8.Габаритный размер модуля (мм)	~110.1x110.1x701

Технические требования

- 1.И14, И14/2
- 2.Размеры для справок
- 3.Сборку модуля производит заказчик.
- 4.Остальные технические требования по ОСТ 95 227-83

7730-00-00-005LL			
Исполнитель	Место	Дата	Масштаб
Разработчик	Спецификация	Изменения	1:1
Проверенный	Собранный	Собранный	1
И.контр.	И.контр.	И.контр.	1
И.контр.	И.контр.	И.контр.	1

Модуль КОРД 15/0.25

Сборочный чертёж

И.контр.

И.контр.

И.контр.

И.контр.


Согласовано: Нач. лаборатории ОНФ

Солдатов А.П.


Контур

Формат А1



Veto barrel (II)



Veto barrel (II)





Calorimeter




$$\sigma(E)/E = 4.7\%/\sqrt{E(\text{GeV})}$$

$$\sigma_t = 52\text{ps}/\sqrt{E(\text{GeV})}$$

Calorimeter




Calorimeter



Calorimeter





Size across beam	Ø120 cm	Entered circle
Radiation length, X_0	13 mm	
Size along beam	312 mm	24 X_0
Size of strip	15 mm	
Total of channels	1920	160 (plane) x 3 (X,U,W) x 4 (segment)
Full length of fibers	220 km	
Total weight of lead	700 kg	





Resolution

- energy $\sigma_E/E \approx 5.5\%/\sqrt{E}$
- spatial 2.5 mm/ $\sqrt{E}$
- angular 20 mrad/ $\sqrt{E}$



Calorimeter



Simulation of setup KLOD




Simulation of setup KLOD




Simulation of setup KLOD



Scattering calorimeter hit points



Estimation error of z-coordinate KOL decay point as versus of z-coordinate



Simulation of setup KLOD



Background and sensitivity

- No. of background events (at a sensitivity of $\text{Br}(K_L^0 \rightarrow \pi^0 \nu \bar{\nu}) = 2 \times 10^{-11}$)
- Other K_L decay with gammas, detection inefficiency of gamma $0.28(\pi^0 \pi^0)$, $< 0.1(\gamma\gamma)$, $< 0.1(\pi^0 \pi^0 \pi^0)$
- K_L decays outside the region $\ll 0.1$
- π^0 production by neutrons in residual gas (10^{-7} Pa) < 0.2
- π^0 production by halo neutrons < 0.1
- One day sensitivity $1/10^8 * 10^4 * .0562 * .181 = 10^{-10}$

Plans

- 2004 – beam line construction at IHEP, production and test of prototypes, simulation.
- 2005 – end of beam construction, measurement of beam characteristics, production of detectors and units of setup, preparation of experimental zone.
- 2006 – setup assembly, test of setup and first run.
- 2007 – runs, data analysis, first results.

Summary

- There is a possibility to make at IHEP setup for registration of $K_L^0 \rightarrow \pi^0 \nu \bar{\nu}$ decays.
- Sensitivity of setup allows for reasonable time (100 days) to register about 30 (SM) decays at a level of a background near 9 decays.
- R&D for production and test of prototypes of the basic detectors is necessary.
- The further simulation for more exact calculation of signals and background processes is necessary.

Possible scenario

- 2004 E391a Data taking, data analysis
- 2004 –beam line construction at IHEP, production and test of prototypes, simulation.
- 2005 E391a Data taking, data analysis
- 2005 – end of beam construction, measurement of beam characteristics, production of detectors and units of setup, preparation of experimental zone.
- 2006 – setup assembly, test of setup and first run.
- 2006 JPARC Beam line construction
- 2007 – runs, data analysis, first results.
- 2007 JPARC